

## MAGNEX® 130 B

Underwater magnetometer

- Ergonomic design
- Robust, compact, modular design
- Easy to operate
- Saltwater compatible



- Audible / visual indication
- 3 search modes:
  - Dynamic (LOW)
  - Semi-static (MEDIUM)
  - Static (HIGH)

## General

The MAGNEX® 130 B is a further development of its well proven forerunner. The search device is of compact modular design and lightweight. It is easy to operate and simple to learn.

## Operation principle

The MAGNEX® 130 B is a passive iron locator, which detects and indicates local anomalies in the natural magnetic field of the earth. It applies the same passive-differential field strength detection principles as bomb locators designed for land use.

The search equipment has three sensitivity ranges. In range 1 the MAGNEX® 130 B operates on a dynamic detection mode, in range 2 on a semi-static mode and in range 3 on a static mode. On range 1 and 2 the device adjusts itself automatically and does not require any further calibration or adjustment procedures. The static mode offers largest detection range depending on the magnetic signature of the object.

Small ammunition such as 20 mm shells will only be detected in the close vicinity of the locator probe whilst bombs or parts from wrecks may be detected from some metres distance.

## Application

The UW magnetometer MAGNEX® 130 B is designed for the locating of magnetic anomalies in the earth's magnetic field as brought about by, for example, ferrous objects that are concealed on the floor of bodies of water or in the ground. Such objects include pipelines, parts of ships, wrecks or ERW.

The MAGNEX® 130 B is used typically in professional operations by police divers, for the geomagnetic surveying of abandoned hazardous sites and by commercial diving companies.



## Technical data

<b>Power supply</b>	Battery 9 V e-block 6LR61 Rechargeable battery 9 V e-block Ni-MH
<b>Operation time*</b>	battery approx. 16 h rechargeable batt. approx 8 h
<b>Charging time rechargeable battery</b>	approx. 4 h with 70 mA
<b>Temperature range</b>	approx. -15 °C to +50 °C
<b>Length Diameter</b>	approx. 985 mm approx. 62 mm
<b>Weight with headset Weight with case</b>	approx. 1,650 g approx. 4,950 g
<b>Pressure water proof</b>	approx. 7 bar, 60 m
<b>Field direction detection</b>	audio via pulsing of the signal tone, audio resolution (stage 3) approx. 10 nT

\* depends of temperature and battery type

EBINGER Prüf- und Ortungstechnik GmbH

[www.ebinger.org](http://www.ebinger.org)

### Technology center & Sales Germany / Benelux

Vulkanstraße 14 · 54578 Wiesbaum · Germany  
Tel. +49 6593 9989-40  
Fax +49 6593 9989-450  
E-Mail: [eifel@ebingergmbh.de](mailto:eifel@ebingergmbh.de)

### Headquarter & Sales international

Hansestr. 13 & 19 · 51149 Köln · Germany  
Tel. +49 2203 977-100  
Fax +49 2203 36062  
E-Mail: [info@ebinger.org](mailto:info@ebinger.org)

Copyright 2013 © EBINGER Prüf- und Ortungstechnik GmbH, Cologne. Copyrights, design rights and brand name rights: Documents, software and designs of EBINGER Prüf- und Ortungstechnik GmbH may be not reproduced, copied or published either in part or in whole unless the written agreement of EBINGER Prüf- und Ortungstechnik GmbH thereto is held. Photos: EB archive and Guido Schiefer. EBEX®, EFIS®, EPAD®, EPAS®, MAGNEX®, MAILEX®, PIDD®, TREX®, UPEX®, UWEX® are registered trademarks of EBINGER Prüf- und Ortungstechnik GmbH, Cologne. Changes, errors and printing errors reserved! The general terms of business of EBINGER Prüf- und Ortungstechnik GmbH hold good. Printed in Germany.

PIEBMAGNEX130B102013E

